

Appl. No. 10/538240  
Reply to Action dated October 16, 2007  
Page 2

RECEIVED  
CENTRAL FAX CENTER  
MAR 17 2008

**Amendments to the Claims:**

This listing of claims will replace all prior versions and listings of claims in the application.

**Listing of Claims:**

1. (Currently Amended) An optical conduction unit, comprising:  
an optical conduction body; and  
a reflector;

wherein said optical conduction body includes a light incidence surface for receiving light from a light source, a light outgoing surface extending in the prescribed x direction to cause the light that propagated from said light incidence surface inside the optical conduction body to go out to the outside, and a pair of side surfaces joined to the light outgoing surface and extending in the x direction;

wherein said reflector includes a first member and a second member for sandwiching said optical conduction body in the y direction perpendicular to the x direction and for covering said pair of side surfaces; [[and]]

wherein said first member comprises first fitting means for mating with a portion of said optical conduction body in the y direction, second fitting means for mating with another portion of said optical conduction body in the x direction, third fitting means for mating with a portion of said second member in the y direction, and fourth fitting means for mating with another portion of said second member in the x direction;

wherein said optical conduction body further includes a main region having said light outgoing surface and said pair of side surfaces and an auxiliary region joined in the x direction to the main region;

wherein said auxiliary region includes said light incidence surface and a light reflecting surface for reflecting the light that propagated from said light incidence surface inside the auxiliary region toward said main region and is configured so that the light that propagated from said auxiliary region inside said main region goes out to the outside from said light outgoing surface, while propagating in the x direction;

Appl. No. 10/538240

Reply to Action dated October 16, 2007

Page 3

wherein said first member further comprises a body section adjacent to said optical conduction body and extending in the x direction and a first wall section and a second wall section protruding in the y direction from the body section and facing each other via a gap; and wherein said first fitting means comprises said first and second wall sections and has said auxiliary region inserted between the first and second wall sections.

2-3. (Cancelled)

4. (Currently Amended) The optical conduction unit according to claim [[3]] 1, wherein said first wall section covers said light reflecting surface.

5. (Currently Amended) The optical conduction unit according to claim [[3]] 1, wherein said main region comprises an end surface facing in the x direction and said first member comprises a third wall section for covering said end surface.

6. (Previously Presented) The optical conduction unit according to claim 5, wherein a first protrusion or orifice having a central axis thereof extending in the x direction is provided in said end surface, and wherein said second fitting means is an orifice or a protrusion provided in said third wall section so as to mate with said first protrusion or orifice.

7. (Original) The optical conduction unit according to claim 6, wherein at one end portion of said second member in the x direction, a second protrusion or orifice having a central axis thereof extending in the y direction is provided, and at the other end portion of said second member in the x direction, a third protrusion or orifice having a central axis thereof extending in the x direction is provided;

wherein said third means is an orifice or a protrusion provided in said first member so as to mate with said second protrusion or orifice; and

wherein said fourth fitting member is an orifice or protrusion provided in the third wall section of said first member so as to mate with said third protrusion or orifice.

Appl. No. 10/538240  
Reply to Action dated October 16, 2007  
Page 4

8. (Original) The optical conduction unit according to claim 7, wherein said third wall section can deform elastically in the x direction.

9. (Currently Amended) The optical conduction unit according to claim 1, wherein said reflector ~~[[has]]~~ includes a tubular portion extending from ~~surrounding from all four sides the~~ region facing said light incidence surface.

10. (Original) The optical conduction unit according to claim 1, wherein said first and second members are made from a white resin.

11. (Currently Amended) An image reading device comprising a light source, an optical conduction unit for illuminating light emitted from the light source toward a reading line of a document, a plurality of sensor ~~[[IC]]~~ integrated circuit (IC) chips for receiving the light reflected from said reading line and outputting an image signal, and a case accommodating the light source, the optical conduction unit, and the plurality of sensor IC chips;

wherein said optical conduction unit comprises an optical conduction body and a reflector;

wherein said optical conduction body includes a light incidence surface for receiving light from a light source, a light outgoing surface extending in the prescribed x direction to cause the light that propagated from said light incidence surface inside the optical conduction body to go out to the outside, and a pair of side surfaces joined to the light outgoing surface and extending in the x direction;

wherein said reflector includes a first member and a second member for sandwiching said optical conduction body in the y direction perpendicular to the x direction and for covering said pair of side surfaces; and

wherein said first member comprises first fitting means for mating with a portion of said optical conduction body in the y direction, second fitting means for mating with another portion of said optical conduction body in the x direction, third fitting means for mating with a portion of said second member in the y direction, and fourth fitting means for mating with another portion of said second member in the x direction.